VICTORIA
STATE OF THE ART

PRESTANDAFÖRKLARING
enligt förordning (EU) 305/2011
№ 10-11-CPR-2025

1. Produkttypens unika identifieringskod:	Riktnummer 27 – rumsvärmare som eldas med fast bränsle Typ B (БДС EN 16510-1:2023) **Taro F, Taro FS, Taro 2F, Taro 2FS, Comfort F, Comfort KF**
2. Typ-, parti- eller serienummer eller annan beteckning som möjliggör identifiering av byggprodukten enligt artikel 11 (4):	Serienummer (se produktskylten)
3. Avsedd användning eller användningar av byggprodukten, i enlighet med den tillämpliga harmoniserade tekniska specifikationen, enligt tillverkarens anvisningar:	Rumsvärmare eldad med fast bränsle utan varmvattenförsörjning, för intermittent förbränning med stängda branddörrar
4. Tillverkarens namn, registrerat handelsnamn eller registrerat varumärke och kontaktadress enligt artikel 11 (5):	**Victoria-05 Ltd.** 1B Ivan Momchilov Str.,5100 Gorna Oryahovitsa Republic of Bulgaria, E-mail: info@v05.bg
5. System eller system för bedömning och verifiering av byggproduktens prestanda enligt bilaga V:	System 3
6. Om prestandadeklarationen gäller en byggprodukt som omfattas av en harmoniserad standard:	**Kontrol 94 Ltd.** 2 Mladost Str., 5100 Gorna Oryahovitsa Republiken Bulgarien, Organ: NB1879 Bedömningsrapport av prestanda: 1879-AoP-HD-0026/24.10.2025 Testrapport: NB 1879-K-15-2025/ 24.10.2025

DEKLARERAD PRESTANDA

Harmoniserad teknisk specifikation		**БДС EN 16510-2-1:2023**	
Väsentliga egenskaper	**Enhet**	**Prestanda**	
		Nominell värmeeffekt	**Dellastens värmeeffekt**
Den maximala belastningen på en skorsten som apparaten får bära (mchim)	kg	20	
Minsta avstånd till brännbart material:			
Från sidorna (dS)	mm	500	
Bakifrån (dR)	mm	400	
Framifrån (dP)	mm	1100	
Under botten (dB)	mm	0	
Från toppen till taket (dC)	mm	750	
Från framsidan till sidans främre strålningsarea (dL)	mm	900	
Från framsidan till botten av strålningsområdet (dF)	mm	500	
Skyddande isolering(ar)	mm	NPD	
Utsläpp vid 13 % O2:			
Kolmonoxidutsläpp (CO)	mg/m3	≤1500	NPD
Kväveoxider (NOx)	mg/m3	≤200	NPD
Organiskt gasformigt kol (OGC)	mg/m3	≤120	NPD
Partiklar (PM)	mg/m3	≤40	NPD
Data för skorstensinstallation:			
Rökgasutloppstemperaturen (Tsnom)/(Tspart)	°C	250	NPD
Minsta rökkanalsdrag (pnom)/(ppart)	Pa	12	NPD
Rökgasmassflödet (Φf,g nom)/(Φf,g del)	g/s	10,5	NPD
Brandsäkerhetsdata vid installation i skorsten:			
Skorstensbeteckning	-	T400G	
Värmeeffekt och verkningsgrad:			
Nominell rumsvärmeeffekt (PSHnom)/(PSHpart)	kW	9,51	NPD
Nominell vatteneffekt (Pwnom)/(Pwpart)	kW	NPD	NPD
Verkningsgrad (ηnom)/(ηpart)	%	≥75	≥75
Effektivitet i rumsuppvärmning och energieffektivitet:			
Säsongsbunden verkningsgrad för rumsuppvärmning vid nominell värmeeffekt (ηs)	%	≥65	
Energieffektivitetsindex (EEI)	-	103	
Energieffektivitetsklass	-	A	
Förbrukningen av elektrisk hjälpenergi (elmax)/(elmin)	kW	NPD	NPD
Förbrukningen av elektrisk hjälpenergi i standby-läge (elsb)	kW	NPD	
Miljömässig hållbarhet		NPD	

Produktens prestanda som anges i punkterna 1 och 2 överensstämmer med den deklarerade prestandan i punkt 8. Denna prestandadeklaration utfärdas på ensamt ansvar av den tillverkare som anges i punkt 4. Undertecknad för och på tillverkarens vägnar av:

24.10.2025г.
Gorna Oryahovitsa

Dimitar Nenov
Manager

Dimitar Ivanov Nenov
Digitally signed by Dimitar Ivanov Nenov
Date: 2025.12.19 10:18:32 +02'00'

Maskinöversättning – ej granskad.
Oförändrat original finns i slutet.

DECLARATION OF PERFORMANCE
according to Regulation (EC) 305/2011
№ 10-11-CPR-2025

1.Unique identification code of the product-type:	Area code 27 – roomheaters fired by solid fuel Type B (БДС EN 16510-1:2023) **Taro F, Taro FS, Taro 2F, Taro 2FS, Comfort F, Comfort KF**
2.Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4):	Serial № (see data plate on the product)
3.Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Roomheater fired by solid fuel without hot water supply, for intermittent burning with firedoors closed
4.Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant Article 11 (5):	**Victoria-05 Ltd.** 1B Ivan Momchilov Str.,5100 Gorna Oryahovitsa Republic of Bulgaria, E-mail: info@v05.bg
5.System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	System 3
6.In case of the declaration of performance concerning a construction product covered by a harmonized standard:	**Kontrol 94 Ltd.** 2 Mladost Str., 5100 Gorna Oryahovitsa Republic of Bulgaria, Body: NB1879 Assessment of performance report: 1879-AoP-HD-0026/24.10.2025 Test report: NB 1879-K-15-2025/ 24.10.2025

DECLARED PERFORMANCE

Harmonized technical specification		**БДС EN 16510-2-1:2023**	
Essential characteristics	**Unit**	**Performance**	
		Nominal heat output	**Part load heat output**
The maximum load of a chimney the appliance may carry (mchim)	kg	20	
The minimum distances to combustible material:			
From the sides (dS)	mm	500	
From the rear (dR)	mm	400	
From the front (dP)	mm	1100	
Below the bottom (dB)	mm	0	
From the top to the ceiling (dC)	mm	750	
From the front to side front radiation area (dL)	mm	900	
From the front to bottom front radiation area (dF)	mm	500	
Protective insulation (s)	mm	NPD	
Emissions at 13% O_2:			
Carbon monoxide emission (CO)	mg/m3	≤1500	NPD
Nitrogen oxides (NOx)	mg/m3	≤200	NPD
Organic gaseous carbon (OGC)	mg/m3	≤120	NPD
Particulate matter (PM)	mg/m3	≤40	NPD
Chimney installation data:			
The flue gas outlet temperature (Tsnom)/(Tspart)	°C	250	NPD
Minimum flue draught (pnom)/(ppart)	Pa	12	NPD
The flue gas mass flow (Φf,g nom)/(Φf,g part)	g/s	10,5	NPD
Fire safety data when installing to chimney:			
Chimney designation	-	T400G	
Heat output and efficiency:			
The nominal space heat output (PSHnom)/(PSHpart)	kW	9,51	NPD
The nominal water output (Pwnom)/(Pwpart)	kW	NPD	NPD
Efficiency (ηnom)/(ηpart)	%	≥75	≥75
Space heating efficiency and energy efficiency:			
Seasonal space heating efficiency at nominal heat output (ηs)	%	≥65	
Energy efficiency index (EEI)	-	103	
Energy efficiency class	-	A	
The consumption of electrical auxiliary energy (elmax)/(elmin)	kW	NPD	NPD
The consumption of electrical auxiliary energy at standby (elsb)	kW	NPD	
Environmental sustainability		NPD	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:

24.10.2025г.
Gorna Oryahovitsa

Dimitar Nenov
Manager

Dimitar Ivanov Nenov
Digitally signed by Dimitar Ivanov Nenov
Date: 2025.12.19 10:18:32 +02'00'