VICTORIA
STATE OF THE ART

# PRESTANDAFÖRKLARING
## enligt förordning (EU) 305/2011
## № 10-3-CPR-2025

| | |
|---|---|
| 1. Produkttypens unika identifieringskod: | Riktnummer 27 – rumsvärmare som eldas med fast bränsle<br>Typ B (БДС EN 16510-1:2023)<br>**Rubin** |
| 2. Typ-, parti- eller serienummer eller annan beteckning som möjliggör identifiering av byggprodukten enligt artikel 11 (4): | Serienummer (se produktskylten) |
| 3. Avsedd användning eller användningar av byggprodukten, i enlighet med den tillämpliga harmoniserade tekniska specifikationen, enligt tillverkarens anvisningar: | Rumsvärmare eldad med fast bränsle utan varmvattenförsörjning, för intermittent förbränning med stängda branddörrar |
| 4. Tillverkarens namn, registrerat handelsnamn eller registrerat varumärke och kontaktadress enligt artikel 11 (5): | **Victoria-05 Ltd.**<br>1B Ivan Momchilov Str.,5100 Gorna Oryahovitsa<br>Republic of Bulgaria, E-mail: info@v05.bg |
| 5. System eller system för bedömning och verifiering av byggproduktens prestanda enligt bilaga V: | System 3 |
| 6. Om prestandadeklarationen gäller en byggprodukt som omfattas av en harmoniserad standard: | **Kontrol 94 Ltd.**<br>2 Mladost Str., 5100 Gorna Oryahovitsa Republiken Bulgarien, Organ: NB1879 Bedömningsrapport av prestanda: 1879-AoP-HD-0036/28.10.2025 Testrapport: NB 1879-K-09-2023/28.04.2023 |

**DEKLARERAD PRESTANDA**

| **Harmoniserad teknisk specifikation** | | **БДС EN 16510-2-1:2023** | |
|---|---|---|---|
| **Väsentliga egenskaper** | **Enhet** | **Prestanda** | |
| | | **Nominell värmeeffekt** | **Dellastens värmeeffekt** |
| Den maximala belastningen på en skorsten som apparaten får bära (mchim) | kg | 20 | |
| **Minsta avstånd till brännbart material:** | | | |
| Från sidorna (dS) | mm | 500 | |
| Bakifrån (dR) | mm | 500 | |
| Framifrån (dP) | mm | 1700 | |
| Under botten (dB) | mm | 40 | |
| Från toppen till taket (dC) | mm | 900 | |
| Från framsidan till sidans främre strålningsarea (dL) | mm | 900 | |
| Från framsidan till botten av strålningsområdet (dF) | mm | 1200 | |
| Skyddande isolering(ar) | mm | NPD | |
| **Utsläpp vid 13 % O2:** | | | |
| Kolmonoxidutsläpp (CO) | mg/m3 | ≤1500 | NPD |
| Kväveoxider (NOx) | mg/m3 | ≤200 | NPD |
| Organiskt gasformigt kol (OGC) | mg/m3 | ≤120 | NPD |
| Partiklar (PM) | mg/m3 | ≤40 | NPD |
| **Data för skorstensinstallation:** | | | |
| Rökgasutloppstemperaturen (Tsnom)/(Tspart) | °C | 302 | NPD |
| Minsta rökkanalsdrag (pnom)/(ppart) | Pa | 12 | NPD |
| Rökgasmassflödet (Φf,g nom)/(Φf,g del) | g/s | 10,8 | NPD |
| **Brandsäkerhetsdata vid installation i skorsten:** | | | |
| Skorstensbeteckning | - | T400G | |
| **Värmeeffekt och verkningsgrad:** | | | |
| Nominell rumsvärmeeffekt ( PSHnom )/( PSHpart ) | kW | 11,40 | NPD |
| Nominell vatteneffekt (Pwnom)/(Pwpart) | kW | NPD | NPD |
| Verkningsgrad (ηnom)/(ηpart) | % | ≥75 | ≥75 |
| **Effektivitet i rumsuppvärmning och energieffektivitet:** | | | |
| Säsongsbunden verkningsgrad för rumsuppvärmning vid nominell värmeeffekt (ηs) | % | ≥65 | |
| Energieffektivitetsindex (EEI) | - | 102 | |
| Energieffektivitetsklass | - | A | |
| Förbrukningen av elektrisk hjälpenergi (elmax)/(elmin) | kW | NPD | NPD |
| Förbrukningen av elektrisk hjälpenergi i standby-läge (elsb) | kW | NPD | |
| **Miljömässig hållbarhet** | | NPD | |

Produktens prestanda som anges i punkterna 1 och 2 överensstämmer med den deklarerade prestandan i punkt 8. Denna prestandadeklaration utfärdas på ensamt ansvar av den tillverkare som anges i punkt 4. Undertecknad för och på tillverkarens vägnar av:

28.10.2025г.
Gorna Oryahovitsa

Dimitar Nenov
Manager

Dimitar Ivanov Nenov

Digitally signed by Dimitar Ivanov Nenov
Date: 2025.12.19 10:17:02 +02'00'

Maskinöversättning – ej granskad.
Oförändrat original finns i slutet.

VICTORIA
STATE OF THE ART

# DECLARATION OF PERFORMANCE
## according to Regulation (EC) 305/2011
## № 10-3-CPR-2025

| | |
|---|---|
| 1.Unique identification code of the product-type: | Area code 27 – roomheaters fired by solid fuel<br>Type B (БДС EN 16510-1:2023)<br>**Rubin** |
| 2.Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4): | Serial № (see data plate on the product) |
| 3.Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: | Roomheater fired by solid fuel without hot water supply, for intermittent burning with firedoors closed |
| 4.Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant Article 11 (5): | **Victoria-05 Ltd.**<br>1B Ivan Momchilov Str.,5100 Gorna Oryahovitsa<br>Republic of Bulgaria, E-mail: info@v05.bg |
| 5.System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: | System 3 |
| 6.In case of the declaration of performance concerning a construction product covered by a harmonized standard: | **Kontrol 94 Ltd.**<br>2 Mladost Str., 5100 Gorna Oryahovitsa<br>Republic of Bulgaria, Body: NB1879<br>Assessment of performance report: 1879-AoP-HD-0036/28.10.2025<br>Test report: NB 1879-K-09-2023/ 28.04.2023 |

**DECLARED PERFORMANCE**

| **Harmonized technical specification** | | **БДС EN 16510-2-1:2023** | |
|---|---|---|---|
| **Essential characteristics** | **Unit** | **Performance** | |
| | | **Nominal heat output** | **Part load heat output** |
| The maximum load of a chimney the appliance may carry (mchim) | kg | 20 | |
| **The minimum distances to combustible material:** | | | |
| From the sides (dS) | mm | 500 | |
| From the rear (dR) | mm | 500 | |
| From the front (dP) | mm | 1700 | |
| Below the bottom (dB) | mm | 40 | |
| From the top to the ceiling (dC) | mm | 900 | |
| From the front to side front radiation area (dL) | mm | 900 | |
| From the front to bottom front radiation area (dF) | mm | 1200 | |
| Protective insulation (s) | mm | NPD | |
| **Emissions at 13% $O_2$:** | | | |
| Carbon monoxide emission (CO) | mg/m3 | ≤1500 | NPD |
| Nitrogen oxides (NOx) | mg/m3 | ≤200 | NPD |
| Organic gaseous carbon (OGC) | mg/m3 | ≤120 | NPD |
| Particulate matter (PM) | mg/m3 | ≤40 | NPD |
| **Chimney installation data:** | | | |
| The flue gas outlet temperature (Tsnom)/(Tspart) | °C | 302 | NPD |
| Minimum flue draught (pnom)/(ppart) | Pa | 12 | NPD |
| The flue gas mass flow (Φf,g nom)/(Φf,g part) | g/s | 10,8 | NPD |
| **Fire safety data when installing to chimney:** | | | |
| Chimney designation | - | T400G | |
| **Heat output and efficiency:** | | | |
| The nominal space heat output (PSHnom)/(PSHpart) | kW | 11,40 | NPD |
| The nominal water output (Pwnom)/(Pwpart) | kW | NPD | NPD |
| Efficiency (ηnom)/(ηpart) | % | ≥75 | ≥75 |
| **Space heating efficiency and energy efficiency:** | | | |
| Seasonal space heating efficiency at nominal heat output (ηs) | % | ≥65 | |
| Energy efficiency index (EEI) | - | 102 | |
| Energy efficiency class | - | A | |
| The consumption of electrical auxiliary energy (elmax)/(elmin) | kW | NPD | NPD |
| The consumption of electrical auxiliary energy at standby (elsb) | kW | NPD | |
| **Environmental sustainability** | | NPD | |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:

28.10.2025г.
Gorna Oryahovitsa

Dimitar Nenov
Manager

Dimitar Ivanov Nenov
Digitally signed by Dimitar Ivanov Nenov
Date: 2025.12.19 10:17:02 +02'00'